

PTP 820S Licensed Microwave Radio

QUICK LOOK:

PTP 820S, single core radio with All Outdoor core radio capable of 2048 QAM with ACM

- Support 6-38 GHz
- Support 1+0, 1+1 HSB, 2+0 SP or DP
- Support Advance Frequency reuse



Radio

6-38 GHz

1+0, 1+1 HSB, 2+0 SP or DP

Multi-Band (PTP 850E, PTP 820E)

Radio Features

Protection: 1+1 HSB

QPSK to 2048 QAM w/ACM

Advanced Frequency Reuse (AFR)

Ethernet

Ethernet Interfaces

Traffic Interfaces – 1 x 10/100/1000Base-T (RJ-45) and 2 x 1000base-X (SFP) or 2 x 10/100/1000 Base-T (electrical SFP)

Management Interface - 1 x 10/100 Base-T (RJ-45)

Optical SFP Types - Optical 1000Base-LX (1310 nm) or SX (850nm)

Note: SFP devices must be of industrial grade (-40°C to +85°C)

Ethernet Features

MTU – 9600 Bytes

Quality of Service

- Multiple Classification criteria (VLAN ID, p-bits, IPv4, DSCP, IPv6 TC, MPLS EXP)

- 8 priority queues

- Deep buffering (configurable up to 64 Mbit per queue)

- WRED

- P-bit marking/remarking

4K VLANs

VLAN add/remove/translate

Frame Cut Through – controlled latency and PDV for delay sensitive applications

Header De-Duplication – Capacity boosting by eliminating inefficiency in all layers (L2, MPLS, L3, L4, Tunneling – GTP for LTE, GRE)

Y.1731 Ethernet OAM

Y.1731 Ethernet Bandwidth Notification (ETH-BN)

Adaptive Bandwidth Notification (ABN)

PTP 820S Licensed Microwave Radio

Management Protocols

SNMP

REST

SDN Support: NETCONF/YANG

Synchronization

Synchronization Distribution

Sync Distribution over any traffic interface (GE/FE)

Sync-E (ITU-T G.8261, G.8262)

SSM/ESMC Support for ring/mesh applications (ITU-T G.8264)

Sync-E Regenerator mode, providing PRC grade (ITU-T G.811) performance for smart pipe applications.

IEEE-1588

Optimized Transport for reduced PDV

IEEE-1588 TC

Security

AES 256-bit Encryption

Secured protocols (HTTPS, SNMPV3, SSH, SFTP)

Radius authentication and authorization

TACACS+ authentication and authorization (session-based)

Standard

MEF

Carrier Ethernet 2.0

Supported Ethernet Standards

10/100/1000base-T/X (IEEE 802.3)

Ethernet VLANs (IEEE 802.3ac)

Virtual LAN (VLAN, IEEE 802.1Q)

Class of service (IEEE 802.1p)

Provider bridges (QinQ – IEEE 802.1ad)

Link aggregation (IEEE 802.3ad)

Auto MDI/MDIX for 1000baseT

RFC 1349: IPv4 TOS

RFC 2474: IPv4 DSCP

RFC 2460: IPv6 Traffic Classes

Standards Compliance

EMC: EN 301 489-1, EN 301 489-4, Class B (Europe), FCC 47 CFR, part 15, class B (US), ICES-003, Class B (Canada), TEC/EMI/TEL-001/01, Class B (India)

Surge: EN61000-4-5, Class 4 (for PWR and ETH1/PoE ports)

Safety: EN 60950-1, IEC 60950-1, UL 60950-1, CSA-C22.2 No.60950-1, EN 60950-22, UL 60950-22, CSAC22.2.60950-22

Ingress Protection: IP66-compliant

Storage: ETSI EN 300 019-1-1 Class 1.2

Transportation: ETSI EN 300 019-1-2 Class 2.3

Technical

Mechanical Specifications

Dimensions: 230mm(H), 233mm(W), 98mm(D), 6.0kg;

9.05”(H), 9.07”(W), 3.86”(D), 13.23 lbs.

Pole Diameter Range (for Remote Mount Installation):

8.89 cm – 11.43 cm; 3.5” – 4.5”

Environmental Specifications

-33°C to +55°C (-45°C to +60°C extended);

-27°F to +131°F (-49°F to +140°F extended)

Power Input Specifications

Standard Input: -48 VDC

IDU DC Input range: -40 to -60 VDC

Power Consumption Specifications

Maximum Power Consumption: 6-11 GHz: 35W; 13-38 GHz: 42W

PTP 820S Licensed Microwave Radio

Transmit Power (dBm)										
Transmit Power	6 GHz	7 GHz	8 GHz	10-11 GHz	13-15 GHz	18 GHz	23 GHz	24 GHz UL HP	26 GHz	28-38 GHz
QPSK	28	28	28	26	24	22	20	-17	21	18
8 PSK	28	28	28	26	24	22	20	-17	21	18
16 QAM	28	27	27	26	23	21	20	-17	20	17
32 QAM	27	26	26	25	22	20	20	-17	19	16
64 QAM	27	26	26	25	22	20	20	-17	19	16
128 QAM	27	26	26	25	22	20	20	-17	19	16
256 QAM	27	26	24	25	20	20	18	-17	17	14
512 QAM	25	24	24	24	20	18	18	-17	17	14
1024 QAM	25	24	24	23	20	18	17	-17	16	13
2048 QAM	23	22	22	21	18	16	16	-17	15	12

Receive Sensitivity															
	3.5 & 5 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-96.5	-96.0	-96.0	-96.0	-95.5	-96.5	-95.5	-94.5	-96.0	-95.0	-94.5	-94.5	-94.5	-94.0	-94.0
16 QAM	-90.0	-89.0	-89.0	-89.0	-89.0	-89.5	-88.5	-88.0	-89.0	-88.0	-87.5	-88.0	-87.5	-87.5	-87.0
32 QAM	-86.5	-85.5	-85.5	-85.5	-85.5	-86.0	-85.0	-84.5	-85.5	-84.5	-84.0	-84.5	-84.0	-84.0	-83.5
64 QAM	-83.0	-82.5	-82.5	-82.0	-83.0	-82.0	-81.0	-82.5	-81.5	-81.0	-81.0	-81.0	-81.0	-80.5	-80.5
128 QAM	-79.5	-79.0	-79.0	-78.5	-79.5	-78.5	-77.5	-79.0	-78.0	-77.5	-77.5	-77.5	-77.5	-77.0	-77.0
256 QAM	-76.5	-75.5	-75.5	-75.5	-76.5	-75.0	-74.5	-75.5	-75.0	-74.5	-74.5	-74.5	-74.0	-74.0	-73.5
	7 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-93.5	-93.0	-93.0	-93.0	-92.5	-93.5	-92.5	-91.5	-93.0	-92.0	-91.5	-91.5	-91.5	-91.0	-91.0
8 PSK	-87.5	-87.0	-87.0	-87.0	-86.5	-87.5	-86.5	-85.5	-87.0	-86.0	-85.5	-85.5	-85.5	-85.0	-85.0
16 QAM	-87.0	-86.5	-86.5	-86.5	-86.0	-87.0	-86.0	-85.0	-86.5	-85.5	-85.0	-85.0	-85.0	-84.5	-84.5
32 QAM	-83.5	-83.0	-83.0	-83.0	-82.5	-83.5	-82.5	-81.5	-83.0	-82.0	-81.5	-81.5	-81.5	-81.0	-81.0
64 QAM	-80.5	-80.0	-80.0	-80.0	-79.5	-80.5	-79.5	-78.5	-80.0	-79.0	-78.5	-78.5	-78.5	-78.0	-78.0
128 QAM	-77.5	-76.5	-76.5	-76.5	-76.5	-77.5	-76.0	-75.5	-76.5	-76.0	-75.5	-75.5	-75.0	-75.0	-74.5
256 QAM	-74.0	-73.5	-73.5	-73.0	-73.0	-74.0	-73.0	-72.0	-73.5	-72.5	-72.0	-72.0	-72.0	-71.5	-71.5
512 QAM	-72.0	-71.5	-71.5	-71.0	-72.0	-71.0	-70.0	-70.0	-71.5	-70.5	-70.0	-70.0	-70.0	-69.5	-69.5
1024 QAM (strong FEC)	-68.5	-68.0	-68.0	-67.5	-68.5	-67.5	-66.5	-66.5	-68.0	-67.0	-66.5	-66.5	-66.5	-66.0	-66.0
1024 QAM (light FEC)	-68.0	-67.0	-67.0	-67.0	-67.5	-66.5	-66.0	-66.0	-67.0	-66.0	-65.5	-66.0	-65.5	-65.5	-65.0

PTP 820S Licensed Microwave Radio

Receive Sensitivity (dBm @BER=10-6) - continued															
	10 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-92.0	-91.5	-91.5	-91.0	-92.0	-91.0	-90.0	-91.5	-90.5	-87.0	-90.0	-90.0	-89.5	-89.0	
8 PSK	-87.0	-86.0	-86.0	-86.0	-87.0	-85.5	-85.0	-86.0	-85.5	-81.5	-85.0	-84.5	-84.5	-84.0	
16 QAM	-85.5	-85.0	-85.0	-84.5	-85.5	-84.5	-83.5	-85.0	-84.0	-80.5	-83.5	-83.5	-83.0	-82.5	
32 QAM	-82.0	-81.5	-81.5	-81.0	-82.0	-81.0	-80.0	-81.5	-80.5	-77.0	-80.0	-80.0	-79.5	-79.0	
64 QAM	-79.0	-78.5	-78.5	-78.0	-79.0	-77.5	-77.0	-78.5	-77.5	-74.0	-77.0	-77.0	-76.5	-76.0	
128 QAM	-75.5	-75.0	-75.0	-74.5	-75.5	-74.5	-73.5	-75.0	-74.0	-70.5	-73.5	-73.5	-73.0	-72.5	
256 QAM	-72.5	-72.0	-72.0	-71.5	-72.5	-71.5	-70.5	-72.0	-71.0	-67.5	-70.5	-70.5	-70.0	-69.5	
512 QAM	-70.0	-69.5	-69.5	-69.0	-70.0	-68.5	-68.0	-69.5	-68.5	-65.0	-68.0	-68.0	-67.5	-67.0	
1024 QAM (strong FEC)	-67.0	-66.5	-66.5	-66.0	-67.0	-66.0	-65.0	-66.5	-65.5	-62.0	-65.0	-65.0	-64.5	-64.0	
1024 QAM (light FEC)	-66.5	-65.5	-65.5	-65.5	-66.5	-65.0	-64.5	-65.5	-65.0	-61.0	-64.5	-64.0	-64.0	-63.5	
	14 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-90.5	-90.0	-90.0	-89.5	-90.5	-89.5	-88.5	-90.0	-89.0	-88.5	-88.5	-88.5	-88.5	-88.0	-88.0
8 PSK	-84.5	-84.0	-84.0	-83.5	-85.5	-83.5	-82.5	-84.0	-83.0	-82.5	-82.5	-82.5	-82.5	-82.0	-82.0
16 QAM	-83.5	-83.0	-83.0	-82.5	-83.5	-82.5	-81.5	-83.0	-82.0	-81.5	-81.5	-81.5	-81.5	-81.0	-81.0
32 QAM	-80.5	-79.5	-79.5	-79.5	-80.5	-79.0	-78.5	-79.5	-79.0	-78.5	-78.5	-78.5	-78.0	-78.0	-77.5
64 QAM	-77.5	-76.5	-76.5	-76.5	-77.0	-76.0	-75.5	-76.5	-76.0	-75.5	-75.5	-75.5	-75.0	-75.0	-74.5
128 QAM	-74.0	-73.5	-73.5	-73.0	-74.0	-73.0	-72.0	-73.5	-72.5	-72.0	-72.0	-72.0	-72.0	-71.5	-71.5
256 QAM	-71.5	-70.5	-70.5	-70.5	-71.0	-70.0	-69.5	-70.5	-69.5	-69.0	-69.5	-69.5	-69.0	-69.0	-68.5
512 QAM	-68.5	-68.0	-68.0	-67.5	-68.5	-67.5	-66.5	-68.0	-67.0	-66.5	-66.5	-66.5	-66.5	-66.0	-66.0
1024 QAM (strong FEC)	-65.5	-65.0	-65.0	-64.5	-65.5	-64.5	-63.5	-65.0	-64.0	-63.5	-63.5	-63.5	-63.5	-63.0	-63.0
1024 QAM (light FEC)	-65.0	-64.0	-64.0	-64.0	-64.5	-63.5	-63.0	-64.0	-63.5	-63.0	-63.0	-63.0	-62.5	-62.5	-62.0
	20 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-89.0	-88.5	-88.5	-88.0	-89.0	-88.0	-87.0	-88.5	-87.5	-84.0	-87.0	-87.0	-87.0	-86.5	-86.0
8 PSK	-84.0	-83.5	-83.5	-83.0	-84.0	-83.0	-82.0	-83.5	-82.5	-79.0	-82.0	-82.0	-82.0	-81.5	-81.0
16 QAM	-82.5	-82.0	-82.0	-81.5	-82.5	-81.0	-80.5	-82.0	-81.0	-77.5	-80.5	-80.5	-80.5	-80.0	-79.5
32 QAM	-79.0	-78.5	-78.5	-78.0	-79.0	-77.5	-77.0	-78.5	-77.5	-74.0	-77.0	-77.0	-77.0	-76.5	-76.0
64 QAM	-76.0	-75.0	-75.0	-75.0	-76.0	-74.5	-74.0	-75.0	-74.5	-70.5	-74.0	-74.0	-73.5	-73.5	-73.0
128 QAM	-73.0	-72.0	-72.0	-72.0	-73.0	-71.5	-71.0	-72.0	-71.5	-67.5	-71.0	-70.5	-70.5	-70.5	-70.0
256 QAM	-70.0	-69.5	-69.5	-69.0	-70.0	-68.5	-68.0	-69.5	-68.5	-65.0	-68.0	-68.0	-68.0	-67.5	-67.0
512 QAM	-67.5	-66.5	-66.5	-66.5	-67.5	-66.0	-65.5	-66.5	-66.0	-62.0	-65.5	-65.0	-65.0	-65.0	-64.5
1024 QAM (strong FEC)	-64.5	-63.5	-63.5	-63.5	-64.5	-63.0	-62.5	-63.5	-63.0	-59.0	-62.5	-62.0	-62.0	-62.0	-61.5
1024 QAM (light FEC)	-63.5	-63.0	-63.0	-62.5	-63.5	-62.5	-61.5	-63.0	-62.0	-58.5	-61.5	-61.5	-61.5	-61.0	-60.5
2048 QAM	-60.0	-59.5	-59.5	-59.0	-60.0	-59.0	-58.0	-59.5	-58.5	-55.0	-58.0	-58.0	-58.0	-57.5	-57.0

PTP 820S Licensed Microwave Radio

Receive Sensitivity (dBm @BER=10-6) - continued															
	25 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-87.5	-86.5	-86.5	-86.5	-86.5	-87.0	-86.0	-85.5	-86.5	-85.5	-82.0	-85.5	-85.0	-85.0	-84.0
8 PSK	-82.5	-82.0	-82.0	-82.0	-81.5	-82.5	-81.5	-80.5	-82.0	-81.0	-77.5	-80.5	-80.5	-80.0	-79.5
16 QAM	-80.5	-80.0	-80.0	-80.0	-79.5	-80.5	-79.5	-78.5	-80.0	-79.0	-75.5	-78.5	-78.5	-78.0	-77.5
32 QAM	-77.5	-77.0	-77.0	-77.0	-76.5	-77.5	-76.0	-75.5	-77.0	-76.0	-72.5	-75.5	-75.5	-75.0	-74.5
64 QAM	-74.5	-74.0	-74.0	-74.0	-73.5	-74.5	-73.5	-72.5	-74.0	-73.0	-69.5	-72.5	-72.5	-72.0	-71.5
128 QAM	-71.5	-71.0	-71.0	-71.0	-70.5	-71.5	-70.5	-69.5	-71.0	-70.0	-66.5	-69.5	-69.5	-69.0	-68.5
256 QAM	-68.5	-67.5	-67.5	-67.5	-67.5	-68.5	-67.0	-66.5	-67.5	-67.0	-63.0	-66.5	-66.0	-66.0	-65.5
512 QAM	-66.0	-65.0	-65.0	-65.0	-65.0	-66.0	-64.5	-64.0	-65.0	-64.5	-60.5	-64.0	-63.5	-63.5	-63.0
1024 QAM (strong FEC)	-63.0	-62.5	-62.5	-62.0	-62.0	-63.0	-61.5	-61.0	-62.5	-61.5	-58.0	-61.0	-61.0	-60.5	-60.0
1024 QAM (light FEC)	-62.5	-61.5	-61.5	-61.5	-61.5	-62.5	-61.0	-60.5	-61.5	-61.0	-57.0	-60.5	-60.0	-60.0	-59.5
2048 QAM	-58.5	-58.0	-58.0	-57.5	-58.5	-57.0	-56.5	-58.0	-57.0	-57.0	-53.5	-56.5	-56.5	-56.0	-55.5
	28 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-87.5	-87.0	-87.0	-87.0	-86.5	-87.5	-86.5	-85.5	-87.0	-86.0	-85.5	-85.5	-85.5	-85.0	-85.0
8 PSK	-83.0	-82.5	-82.5	-82.5	-82.0	-83.0	-82.0	-81.0	-82.5	-81.5	-81.0	-81.0	-81.0	-80.5	-80.5
16 QAM	-81.0	-80.5	-80.5	-80.5	-80.0	-81.0	-79.5	-79.0	-80.5	-79.5	-79.0	-79.0	-79.0	-78.5	-78.0
32 QAM	-77.5	-77.0	-77.0	-77.0	-76.5	-77.5	-76.0	-75.5	-77.0	-76.0	-75.5	-75.5	-75.5	-75.0	-74.5
64 QAM	-74.5	-74.0	-74.0	-74.0	-73.5	-74.5	-73.0	-72.5	-74.0	-73.0	-72.5	-72.5	-72.5	-72.0	-71.5
128 QAM	-71.5	-70.5	-70.5	-70.5	-70.5	-71.0	-70.0	-69.5	-70.5	-69.5	-69.0	-69.5	-69.0	-69.0	-68.5
256 QAM	-68.5	-67.5	-67.5	-67.5	-67.5	-68.0	-67.0	-66.5	-67.5	-66.5	-66.0	-66.5	-66.0	-66.0	-65.5
512 QAM	-66.0	-65.0	-65.0	-65.0	-65.0	-66.0	-64.5	-64.0	-65.0	-64.5	-64.0	-64.0	-63.5	-63.5	-63.0
1024 QAM (strong FEC)	-63.0	-62.5	-62.5	-62.0	-62.0	-63.0	-61.5	-61.0	-62.5	-61.5	-61.0	-61.0	-61.0	-60.5	-60.0
1024 QAM (light FEC)	-62.0	-61.5	-61.5	-61.0	-61.0	-62.0	-60.5	-60.0	-61.5	-60.5	-60.0	-60.0	-60.0	-59.5	-59.0
2048 QAM	-58.5	-58.0	-58.0	-57.5	-58.5	-57.0	-56.5	-58.0	-57.0	-57.0	-56.5	-56.5	-56.5	-56.0	-55.5
	30 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-87.5	-87.0	-87.0	-87.0	-86.5	-87.5	-86.0	-85.5	-87.0	-86.0	-85.5	-85.5	-85.5	-85.0	-84.5
8 PSK	-82.5	-81.5	-81.5	-81.5	-81.5	-82.5	-81.0	-80.5	-81.5	-81.0	-80.5	-80.5	-80.0	-80.0	-79.0
16 QAM	-81.0	-80.0	-80.0	-80.0	-80.0	-80.5	-79.5	-79.0	-80.0	-79.0	-78.5	-79.0	-78.5	-78.5	-77.5
32 QAM	-77.0	-76.5	-76.5	-76.5	-76.0	-77.0	-76.0	-75.0	-76.5	-75.5	-75.0	-75.0	-75.0	-74.5	-74.0
64 QAM	-74.5	-73.5	-73.5	-73.5	-73.5	-74.0	-73.0	-72.5	-73.5	-72.5	-72.0	-72.5	-72.0	-72.0	-71.0
128 QAM	-71.0	-70.5	-70.5	-70.5	-70.0	-71.0	-70.0	-69.0	-70.5	-69.5	-69.0	-69.0	-69.0	-68.5	-68.0
256 QAM	-68.0	-67.5	-67.5	-67.5	-67.0	-68.0	-67.0	-66.0	-67.5	-66.5	-66.0	-66.0	-66.0	-65.5	-65.0
512 QAM	-66.0	-65.5	-65.5	-65.5	-65.0	-66.0	-64.5	-64.0	-65.5	-64.5	-64.0	-64.0	-64.0	-63.5	-63.0
1024 QAM (strong FEC)	-63.0	-62.0	-62.0	-62.0	-62.0	-62.5	-61.5	-61.0	-62.0	-61.0	-60.5	-61.0	-60.5	-60.5	-59.5
1024 QAM (light FEC)	-62.0	-61.0	-61.0	-61.0	-61.0	-62.0	-60.5	-60.0	-61.0	-60.5	-60.0	-60.0	-59.5	-59.5	-58.5
2048 QAM	-58.0	-57.5	-57.5	-57.5	-57.0	-58.0	-56.5	-56.0	-57.5	-56.5	-56.0	-56.0	-56.0	-55.5	-55.0

PTP 820S Licensed Microwave Radio

Receive Sensitivity (dBm @BER=10-6) - continued															
	40 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-86.0	-85.5	-85.5	-85.5	-85.0	-86.0	-85.0	-84.0	-85.5	-84.5	-84.0	-84.0	-84.0	-83.5	-83.5
8 PSK	-81.0	-80.5	-80.5	-80.5	-80.0	-81.0	-79.5	-79.0	-80.5	-79.5	-79.0	-79.0	-79.0	-78.5	-78.0
16 QAM	-79.5	-79.0	-79.0	-79.0	-78.5	-79.5	-78.0	-77.5	-79.0	-78.0	-77.5	-77.5	-77.5	-77.0	-76.5
32 QAM	-76.0	-75.0	-75.0	-75.0	-75.5	-74.5	-74.0	-74.0	-75.0	-74.0	-73.5	-74.0	-73.5	-73.5	-73.0
64 QAM	-73.0	-72.0	-72.0	-72.0	-72.0	-73.0	-71.5	-71.0	-72.0	-71.5	-71.0	-71.0	-70.5	-70.5	-70.0
128 QAM	-70.0	-69.0	-69.0	-69.0	-69.0	-70.0	-68.5	-68.0	-69.0	-68.5	-68.0	-68.0	-67.5	-67.5	-67.0
256 QAM	-67.0	-66.0	-66.0	-66.0	-66.0	-66.5	-65.5	-65.0	-66.0	-65.0	-64.5	-65.0	-64.5	-64.5	-64.0
512 QAM	-64.0	-63.5	-63.5	-63.0	-64.0	-62.5	-62.0	-63.5	-62.5	-62.0	-62.0	-62.0	-62.0	-61.5	-61.0
1024 QAM (strong FEC)	-61.5	-61.0	-61.0	-60.5	-61.5	-60.0	-59.5	-61.0	-60.0	-59.5	-59.5	-59.5	-59.5	-59.0	-58.5
1024 QAM (light FEC)	-60.5	-60.0	-60.0	-59.5	-60.5	-59.5	-58.5	-60.0	-59.0	-58.5	-58.5	-58.5	-58.5	-58.0	-58.0
2048 QAM	-58.0	-57.0	-57.0	-57.0	-58.0	-56.5	-56.0	-57.0	-56.5	-56.0	-56.0	-56.0	-55.5	-55.5	-55.0
	50 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-85.5	-84.5	-84.5	-84.5	-84.5	-85.0	-84.0	-83.5	-84.5	-83.5	-80.0	-83.5	-83.0	-83.0	-82.5
8 PSK	-80.0	-79.5	-79.5	-79.5	-79.0	-80.0	-79.0	-78.0	-79.5	-78.5	-75.0	-78.0	-78.0	-78.0	-77.5
16 QAM	-78.5	-77.5	-77.5	-77.5	-77.5	-78.0	-77.0	-76.5	-77.5	-76.5	-73.0	-76.5	-76.0	-76.0	-75.5
32 QAM	-74.5	-74.0	-74.0	-74.0	-73.5	-74.5	-73.5	-72.5	-74.0	-73.0	-69.5	-72.5	-72.5	-72.5	-72.0
64 QAM	-71.5	-70.5	-70.5	-70.5	-70.5	-71.5	-70.0	-69.5	-70.5	-70.0	-66.0	-69.5	-69.0	-69.0	-68.5
128 QAM	-68.5	-68.0	-68.0	-68.0	-67.5	-68.5	-67.5	-66.5	-68.0	-67.0	-63.5	-66.5	-66.5	-66.5	-66.0
256 QAM	-66.0	-65.0	-65.0	-65.0	-65.0	-66.0	-64.5	-64.0	-65.0	-64.5	-60.5	-64.0	-63.5	-63.5	-63.0
512 QAM	-63.5	-63.0	-63.0	-63.0	-62.5	-63.5	-62.0	-61.5	-63.0	-62.0	-58.5	-61.5	-61.5	-61.5	-61.0
1024 QAM (strong FEC)	-60.0	-59.5	-59.5	-59.0	-60.0	-58.5	-58.0	-59.5	-58.5	-55.0	-58.0	-58.0	-58.0	-58.0	-57.5
1024 QAM (light FEC)	-59.0	-58.0	-58.0	-58.0	-59.0	-57.5	-57.0	-58.0	-57.5	-53.5	-57.0	-56.5	-56.5	-56.5	-56.0
2048 QAM	-57.0	-56.0	-56.0	-56.0	-56.0	-56.5	-55.5	-55.0	-56.0	-55.0	-51.5	-55.0	-54.5	-54.5	-54.0
	56 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-84.0	-83.5	-83.5	-83.5	-83.0	-84.0	-83.0	-82.0	-83.5	-82.5	-82.0	-82.0	-82.0	-81.5	-81.5
8 PSK	-80.0	-79.5	-79.5	-79.5	-79.0	-80.0	-79.0	-78.0	-79.5	-78.5	-78.0	-78.0	-78.0	-77.5	-77.5
16 QAM	-77.5	-77.0	-77.0	-77.0	-76.5	-77.5	-76.5	-75.5	-77.0	-76.0	-75.5	-75.5	-75.5	-75.0	-75.0
32 QAM	-74.5	-73.5	-73.5	-73.5	-73.5	-74.0	-73.0	-72.5	-73.5	-72.5	-72.0	-72.5	-72.0	-72.0	-71.5
64 QAM	-71.0	-70.5	-70.5	-70.5	-70.0	-71.0	-70.0	-69.0	-70.5	-69.5	-69.0	-69.0	-69.0	-68.5	-68.5
128 QAM	-68.5	-67.5	-67.5	-67.5	-67.5	-68.0	-67.0	-66.5	-67.5	-66.5	-66.0	-66.5	-66.0	-66.0	-65.5
256 QAM	-65.0	-64.5	-64.5	-64.5	-64.0	-65.0	-64.0	-63.0	-64.5	-63.5	-63.0	-63.0	-63.0	-62.5	-62.5
512 QAM	-63.0	-62.5	-62.5	-62.5	-62.0	-63.0	-61.5	-61.0	-62.5	-61.5	-61.0	-61.0	-61.0	-60.5	-60.0
1024 QAM (strong FEC)	-59.5	-59.0	-59.0	-59.0	-58.5	-59.5	-58.5	-57.5	-59.0	-58.0	-57.5	-57.5	-57.5	-57.0	-57.0
1024 QAM (light FEC)	-58.5	-58.0	-58.0	-58.0	-57.5	-58.5	-57.5	-56.5	-58.0	-57.0	-56.5	-56.5	-56.5	-56.0	-56.0
2048 QAM	-54.0	-53.5	-53.5	-53.5	-53.0	-54.0	-53.0	-52.0	-53.5	-52.5	-52.0	-52.0	-52.0	-51.5	-51.5

PTP 820S Licensed Microwave Radio

Receive Sensitivity (dBm @BER=10-6) - continued															
	60 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-84.5	-84.0	-84.0	-84.0	-83.5	-84.5	-83.0	-82.5	-84.0	-83.0	-82.5	-82.5	-82.5	-82.0	-81.5
8 PSK	-80.0	-79.0	-79.0	-79.0	-79.0	-79.5	-78.5	-78.0	-79.0	-78.0	-77.5	-78.0	-77.5	-77.5	-77.0
16 QAM	-77.5	-77.0	-77.0	-77.0	-76.5	-77.5	-76.0	-75.5	-77.0	-76.0	-75.5	-75.5	-75.5	-75.0	-74.5
32 QAM	-74.0	-73.0	-73.0	-73.0	-73.0	-73.5	-72.5	-72.0	-73.0	-72.0	-71.5	-72.0	-71.5	-71.5	-71.0
64 QAM	-70.5	-70.0	-70.0	-70.0	-69.5	-70.5	-69.5	-68.5	-70.0	-69.0	-68.5	-68.5	-68.5	-68.0	-68.0
128 QAM	-68.0	-67.0	-67.0	-67.0	-67.0	-67.5	-66.5	-66.0	-67.0	-66.0	-65.5	-66.0	-65.5	-65.5	-65.0
256 QAM	-64.5	-64.0	-64.0	-64.0	-63.5	-64.5	-63.5	-62.5	-64.0	-63.0	-62.5	-62.5	-62.5	-62.0	-62.0
512 QAM	-62.5	-62.0	-62.0	-62.0	-61.5	-62.5	-61.5	-60.5	-62.0	-61.0	-60.5	-60.5	-60.5	-60.0	-60.0
1024 QAM (strong FEC)	-59.0	-58.5	-58.5	-58.5	-58.0	-59.0	-58.0	-57.0	-58.5	-57.5	-57.0	-57.0	-57.0	-56.5	-56.5
1024 QAM (light FEC)	-58.0	-57.5	-57.5	-57.5	-57.0	-58.0	-57.0	-56.0	-57.5	-56.5	-56.0	-56.0	-56.0	-55.5	-55.5
2048 QAM	-55.5	-54.5	-54.5	-54.5	-54.5	-55.0	-54.0	-53.5	-54.5	-53.5	-53.0	-53.5	-53.0	-53.0	-52.5
	80 MHz	6 GHz	7 GHz	8 GHz	10 GHz	11 GHz	13 GHz	15 GHz	18 GHz	23 GHz	24 GHz	26 GHz	28-31 GHz	32 GHz	38 GHz
QPSK	-82.5	-82.0	-82.0	-82.0	-81.5	-82.5	-81.5	-80.5	-82.0	-81.0	-80.5	-80.5	-80.5	-80.0	-80.0
8 PSK	-78.5	-78.0	-78.0	-78.0	-77.5	-78.5	-77.5	-76.5	-78.0	-77.0	-76.5	-76.5	-76.5	-76.0	-76.0
16 QAM	-76.0	-75.5	-75.5	-75.5	-75.0	-76.0	-75.0	-74.0	-75.5	-74.5	-74.0	-74.0	-74.0	-73.5	-73.5
32 QAM	-73.0	-72.0	-72.0	-72.0	-72.0	-72.5	-71.5	-71.0	-72.0	-71.0	-70.5	-71.0	-70.5	-70.5	-70.0
64 QAM	-69.5	-69.0	-69.0	-69.0	-68.5	-69.5	-68.5	-67.5	-69.0	-68.0	-67.5	-67.5	-67.5	-67.0	-67.0
128 QAM	-67.0	-66.0	-66.0	-66.0	-66.0	-66.5	-65.5	-65.0	-66.0	-65.0	-64.5	-65.0	-64.5	-64.5	-64.0
256 QAM	-63.5	-63.0	-63.0	-63.0	-62.5	-63.5	-62.5	-61.5	-63.0	-62.0	-61.5	-61.5	-61.5	-61.0	-61.0
512 QAM	-61.5	-61.0	-61.0	-61.0	-60.5	-61.5	-60.0	-59.5	-61.0	-60.0	-59.5	-59.5	-59.5	-59.0	-58.5
1024 QAM Strong	-58.0	-57.5	-57.5	-57.5	-57.0	-58.0	-57.0	-56.0	-57.5	-56.5	-56.0	-56.0	-56.0	-55.5	-55.5
1024 QAM Light	-57.0	-56.5	-56.5	-56.5	-56.0	-57.0	-56.0	-55.0	-56.5	-55.5	-55.0	-55.0	-55.0	-54.5	-54.5
2048 QAM	-54.0	-53.5	-53.5	-53.5	-53.0	-54.0	-53.0	-52.0	-53.5	-52.5	-52.0	-52.0	-52.0	-51.5	-51.5

Ethernet Throughput (Mbps)						
Modulation	Channel Size	No Compression		L2 Compression		
QPSK	5 MHz	3-4	4-13	10 MHz	13-15	13-48
8 PSK		-	-		19-23	20-73
16 QAM		8-10	9-32		26-32	28-100
32 QAM		11-14	12-43		35-43	37-133
64 QAM		14-17	15-54		43-53	45-164
128 QAM		17-21	18-65		52-63	54-196
256 QAM		19-24	20-74		59-72	62-225
512 QAM		-	-		65-79	68-247
1024 QAM Strong		-	-		68-83	72-260
1024 QAM Light		-	-		73-89	76-276

PTP 820S Licensed Microwave Radio

Ethernet Throughput (Mbps) - continued						
Modulation	Channel Size	No Compression	L2 Compression	Channel Size	No Compression	L2 Compression
QPSK	14 MHz	19-24	20-74	20 MHz	28-34	29-105
8 PSK		29-36	31-112		42-51	44-158
16 QAM		40-49	42-153		57-70	60-217
32 QAM		53-65	56-203		75-92	79-286
64 QAM		66-80	69-249		92-113	97-352
128 QAM		79-97	83-301		112-136	117-424
256 QAM		90-110	95-344		126-155	133-481
512 QAM		100-122	105-380		138-169	145-526
1024 QAM Strong		106-129	111-402		147-180	154-559
1024 QAM Light		112-137	118-426		156-191	164-593
2048 QAM		-	-		166-203	175-633
QPSK	25 MHz	35-43	37-135	28 MHz	43-52	45-162
8 PSK		53-65	56-202		62-76	65-236
16 QAM		72-88	76-275		87-107	92-332
32 QAM		95-117	100-363		115-140	121-437
64 QAM		117-143	123-446		141-173	149-538
128 QAM		141-173	148-538		170-208	179-648
256 QAM		161-197	169-613		196-239	206-745
512 QAM		178-217	187-677		209-255	219-794
1024 QAM Strong		189-231	198-719		228-278	239-866
1024 QAM Light		201-245	211-763		241-295	253-917
2048 QAM		215-263	226-819		263-321	276-1000
QPSK	30 MHz	43-52	45-162	40 MHz	58-71	61-220
8 PSK		62-76	65-236		86-105	90-328
16 QAM		87-107	92-332		117-143	123-446
32 QAM		115-140	121-437		154-189	162-588
64 QAM		141-173	149-538		190-232	199-722
128 QAM		170-208	179-648		229-280	241-873
256 QAM		196-239	206-745		247-302	259-939
512 QAM		209-255	219-794		270-330	284-1000
1024 QAM Strong		228-278	239-866		306-375	322-1000
1024 QAM Light		241-295	253-917		325-398	342-1000
2048 QAM		263-321	276-1000		352-430	370-1000

PTP 820S Licensed Microwave Radio

Ethernet Throughput (Mbps) - continued							
Modulation	Channel Size	No Compression	L2 Compression	Channel Size	No Compression	L2 Compression	
QPSK	50 MHz	70-86	74-267	56 MHz	87-106	91-331	
8 PSK		109-133	114-415		127-155	133-482	
16 QAM		148-181	155-563		176-215	185-670	
32 QAM		186-227	195-707		232-283	243-881	
64 QAM		240-293	252-913		284-348	299-1000	
128 QAM		280-342	294-1000		344-420	361-1000	
256 QAM		332-406	348-1000		397-485	416-1000	
512 QAM		360-440	378-1000		426-521	448-1000	
1024 QAM Strong		392-479	411-1000		464-567	487-1000	
1024 QAM Light		416-509	437-1000		493-602	517-1000	
2048 QAM		449-548	471-1000		534-653	561-1000	
QPSK	60 MHz	87-106	91-331	80 MHz	114-140	120-435	
8 PSK		127-155	133-482		162-198	170-618	
16 QAM		176-215	185-670		231-283	243-880	
32 QAM		232-283	243-881		304-371	319-1000	
64 QAM		284-348	299-1000		371-454	390-1000	
128 QAM		344-420	361-1000		439-536	461-1000	
256 QAM		397-485	416-1000		505-618	531-1000	
512 QAM		427-521	448-1000		555-679	583-1000	
1024 QAM Strong		464-567	487-1000		604-738	634-1000	
1024 QAM Light		493-602	517-1000		641-784	673-1000	
2048 QAM		534-653	561-1000		679-829	713-1000	

ABOUT CAMBIUM NETWORKS

Cambium Networks empowers millions of people with wireless connectivity worldwide. Its wireless portfolio is used by commercial and government network operators as well as broadband service providers to connect people, places and things. With a single network architecture spanning fixed wireless and Wi-Fi, Cambium Networks enables operators to achieve maximum performance with minimal spectrum. End-to-end cloud management transforms networks into dynamic environments that evolve to meet changing needs with minimal physical human intervention. Cambium Networks empowers a growing ecosystem of partners who design and deliver gigabit wireless solutions that just work.